

Quality Polymers from



25 Years of Innovation!

## RANTEC CORPORATION

PO Box 729  
Ranchester, WY 82839

Phone: (307) 655-9565

Fax: (307) 655-9528

www.ranteccorp.com

e-mail: rantec@ranteccorp.com

# C6SJ

## GUAR GUM BASED TACKIFIER

### PRODUCT DESCRIPTION

**C6SJ** is a 100% organic tackifier manufactured from guar gum. **C6SJ** is specifically designed for use as a hydraulically applied erosion control tackifier. **C6SJ** is used as a stand alone temporary erosion control product or with wood, paper, or other native fiber mulches to provide superior bonding strength.

### APPLICATION GUIDELINES

It is recommended that **C6SJ** be applied at 10 to 25 lbs per 1000 gallons of water depending on machine capacity. When used as an overspray for straw, use **C6SJ** more concentrated at the rate of 40 lbs in 1000 gallons per acre with the use of 150 to 300 lbs of mulch as a marker.

### GENERAL USAGE RATES PER ACRE

SLOPE:	FLAT	4:1	3:1	2:1	1:1
LB/ACRE:	30-50	50-80	80-100	100-150	150-220

### MIXING INSTRUCTIONS

1. Add water to tank to cover blades of lower agitator.
2. Add **C6SJ** slowly while filling tank with agitator at high speed.
3. After **C6SJ** is thoroughly mixed, add mulch seed, and fertilizer.

### PACKAGING

**C6SJ** is packaged in 50 lb multi-wall paper bags, 40 bags per pallet with stretched wrapped cover and pallet liner.